

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 481 702 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
01.12.2004 Bulletin 2004/49

(51) Int Cl.7: **A61M 16/06, A61M 16/08**

(21) Application number: **04012752.4**

(22) Date of filing: **28.05.2004**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PL PT RO SE SI SK TR**
Designated Extension States:
AL HR LT LV MK

(30) Priority: **30.05.2003 NZ 52636203**

(71) Applicant: **Fisher & Paykel Healthcare Limited
East Tamaki, Auckland (NZ)**

(72) Inventors:

- **White, Craig Karl
Remuera Auckland (NZ)**
- **Van Beurden, Jason Peter
New Lynn Auckland (NZ)**
- **O'Donnell, Kevin Peter
Hamilton (NZ)**

(74) Representative: **Hoarton, Lloyd Douglas Charles
Forrester & Boehmert,
Pettenkoferstrasse 20-22
80336 München (DE)**

(54) **Breathing assistance apparatus**

(57) A nasal cannula assembly (20) is disclosed having a face mount part (21), in use resting against a user's face, which includes at least one nasal prong (22) capable of being fitted into a person's nares. The cannula assembly (20) also includes a manifold part (24), in fluid communication with the face mount part (21), having a single horizontal side gases entry. In particular, this cannula assembly (20) is for supplying heated, humidified gases to a patient suffering from COPD. A tie

or lanyard (73) is disclosed for use with a breathing assistance apparatus such as a nasal cannula (20), face or nasal mask or tracheostomy connector (69). The tie or lanyard (73) transfers the weight of the conduits supplying gases (95) to the breathing assistance apparatus from the breathing assistance apparatus and distributes it onto the neck of the patient.

EP 1 481 702 A2

Description

FIELD OF INVENTION

[0001] The present invention relates particularly, though not solely, to the delivery of high flow humidified pressurised oxygen and/or air to a patient in need of respiratory support by way of a nasal cannula.

SUMMARY OF THE PRIOR ART

[0002] Nasal cannula generally consist of entry tubing, either symmetric or single sided that lies across the upper lip. Protruding from this tubing are open ended prongs which extend into the nares of the patient to deliver oxygen. Nasal cannulae have the advantage of being more comfortable and acceptable than a face mask to most patients. The existing market for nasal cannula is well serviced by devices suitable for the delivery of gases in the 0 to 5 litre per minute range. These devices are typically supplied by a double entry lumen of small diameter (2-3mm range) that supplies both sides of the nasal cannula and provides even airflow to each nasal prong. These devices work well for the delivery of low humidity gas flows of between 0 to 5 litre per minute and have been well received by patients over the last 30 years.

[0003] Hudson Respiratory Care Incorporated manufactures a nasal cannula that is disclosed in US2,868,199 that consists of a single flow entry nasal cannula. This single flow entry has the advantage of being unobtrusive, and more relevant to delivering humidity than a dual flow entry style of nasal cannula, simply due to the advantage of flow rates and surface area for heat loss. The single flow entry is on the left side only, which causes the user difficulty in use if the flow source is on the opposite side of the user requiring longer lengths of tubing and causing the tube to cross the body. The cannula itself is manufactured as one part only, of PVC plastic. This product is not designed for delivering high flow or high humidity gases. The nasal prongs are less than 3mm in diameter resulting in noise and high velocity jetting of gas causing severe irritation at high flows. These cannulae are difficult to clean inside, are uncomfortable, and the prongs are too rigid for extended therapies.

[0004] US3,754,552 of Sandoz-Wander, Inc discloses a nasal cannula, having two nasal prongs, adapted for the intake of therapeutic gas from either the right or left side of the patient. Here the nasal cannula has a bore within it that feeds each prong. The bore is able to receive a tube for supplying gases to the cannula in either end and in use a plug is required to obstruct the unused end.

[0005] Innomed Technologies, Inc. manufactures a nasal cannula device called the NASALAIRE™. This nasal cannula is a dual flow entry style cannula where two large tubes come from behind the ears, through the

field of vision to the upper lip. In this device air or oxygen travels down a wide bore conduit to the nasal cannula. The NASALAIRE™ creates a physical seal between the nares and itself, and relies on the absence of leaks around itself and the nares to deliver pressure supplied by a continuous positive airway pressure (CPAP) blower to the airway of the wearer. The wearer is required to breathe in and out of the NASALAIRE™, thereby re-breathing some of the exhaled air from the lungs. The NASALAIRE™ is not designed to deliver humidified gases to the patient, being unheated and without insulation of any type. The NASALAIRE™ cannula is uncomfortable especially if a patient rests on the tube, as would happen during sleep, and is also obtrusive.

[0006] The new application of high airflow extended therapies using nasal cannulae generally result in the nasal cannula reaching temperatures in excess of 35 degrees C. Usually cannulae are made from soft polymeric material (for example, silicone) that absorbs heat and does not breathe and therefore sweat is generated under the contact points with the skin. This heat in combination with the polymeric materials waterproof properties results in sweat being trapped against a patient's skin and the patient has the sensation of overheating. The trapped sweat is uncomfortable and could lead to rashes.

[0007] Oxygen is generally supplied as a dry gas, but it is well known in the art to either heat and/or humidify gases before delivering them for breathing by a patient. In particular when delivering oxygen, or an oxygen air mixture, it has proven beneficial to humidify the gases first. In WO 01/41854 of VapoTherm, Inc. a system is disclosed that allows the delivery of humidified oxygen through a nasal cannula. This system uses a narrow bore conduit and nasal cannula with a high resistance to gas flows, thereby requiring the oxygen be of a high pressure. Air, as well as oxygen, can also be passed down the conduit and nasal cannula and it too must be of a high pressure. This system allows the delivery of high flows of oxygen enriched air to the patient, but is limited in the flows achievable due to the narrow bore of the cannula resulting in high resistance gas flow and excessive velocity and noise upon exiting the cannula. Furthermore, the narrowness of the nasal cannula in this system allows the patient to easily expire gases from their nostrils as there is a reasonable gap between the prongs and the patient's nares. Thus positive airway pressure is not created and as such this cannula is not suitable for the treatment of Obstructive Sleep Apnea (OSA).

[0008] In breathing circuits that supply respiratory gases to a patient by way of a patient interface, such as a nasal cannula, mask or tracheal tube, it is common, to have a heated breathing circuit or tube delivering heated and humidified gases to the patient, followed by a short length of non-heated tube close to the patient. This unheated tube may be a short unheated extension tube or catheter mount. The unheated section of tube is

usually intended to be very flexible to reduce torsion or pulling on the patient interface, to allow the gases to cool slightly towards the dew point of the gas, and also to eliminate hot surface temperatures near the patient. As this tube is unheated the temperature of the tube walls are colder than the dew point temperature of the gas, as a result the vapour in the gases passing near these walls will begin to condense out. Over time a build up of condensate close to the patient may lead to a build-up of bacteria which may cause infection. Build up of condensation may also create noise, such as gurgling, which may wake a patient, and in extreme circumstances the fluid build up may cause drowning.

[0009] When providing humidified gases to a patient it is common to use a heated breathing circuit (tubing). This circuit is heavy and can drag and pull on the patient interface. This is more pronounced if the patient is mobile and can be painful and/or dangerous if the patient interface is invasive such as an endotracheal tube. It is common to use a short flexible tube between the heated circuit and patient interface to reduce any torque or twisting. In order to stop the weight pulling on the patient interface, circuit hangers are occasionally used. This is a large extendable metal arm to take the weight. It also has been known in the art to clip part of the tubing to the patient's clothes or bedclothes. Both of these solutions have been found to be quite unsuitable for mobile patients especially when sleeping and turning in bed.

[0010] With patient interfaces such as nasal cannulae the stability of the nasal prongs on the face is very important, as movement of the prongs within the nares can cause severe irritation. Current methods employed to retain a single entry nasal cannula on the face use a simple elastic band of material around the back of the patient's head. This is prone to rotating the nasal cannula relative to the patient's head especially when turning one's head on a pillow. This rotation causes the prongs move within the nares, irritating this sensitive area.

SUMMARY OF THE INVENTION

[0011] It is an object of the present invention to provide a breathing assistance apparatus which goes some way to overcoming the above mentioned disadvantages or which will at least provide the public a useful choice.

[0012] Accordingly in a first aspect the present invention consists in a nasal cannula assembly adapted to deliver gases to a patient comprising:

a face mount part, including at least one nasal prong capable of being fitted into at least one of said patient's nares,
a removable gases flow manifold part in use in fluid communication with said face mount part, said manifold part having a single horizontal side gases entry, in use, in fluid communication with said transport means.

[0013] In a second aspect the present invention may broadly be said to consist in a breathing assistance apparatus comprising:

a pressurised source of gases,
humidification means adapted to, in use, be in fluid communication with said source of gases and adapted to in use humidify said gases,
humidified gases transport means adapted to, in use, be in fluid communication with said humidification means and adapted to in use convey said humidified gases,
heating means disposed within said transport means and adapted to in use heat said gases as they pass through said transport means, and
nasal cannula, adapted to deliver said humidified gases to said patient, said nasal cannula comprising a face mount part, including at least one nasal prong capable of being fitted into at least one of said patient's nares, a removable gases flow manifold part in use in fluid communication with said face mount part, said manifold part having a single horizontal side gases entry, in use, in fluid communication with said transport means.

[0014] The invention consists in the forgoing and also envisages constructions of which the following gives examples.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Preferred forms of the present invention will now be described with reference to the accompanying drawings.

Figure 1 is an illustration of a respiratory humidifier system that may be used with the nasal cannula assembly of the present invention.

Figure 2 is a perspective view of a first form of the nasal cannula assembly of the present invention.

Figure 3 is an exploded perspective view of the first form of the nasal cannula assembly of Figure 2, showing two parts making up the nasal cannula, a face mount part and gases flow manifold part attached to tubing supplying gases to the patient.

Figure 4 is a perspective view of a second form of the nasal cannula assembly of the present invention, showing tubing providing gases supply to a gases flow manifold part and face mount part when in connection.

Figure 5 is a perspective view of the second form of the nasal cannula assembly of Figure 4 where the gases flow manifold part is disengaged from the face mount part.

Figure 6 is a perspective view of the second form of the nasal cannula assembly of Figure 4 where the gases flow manifold part is disengaged from the face mount part, showing the manifold part can be

fitted to either side of the face mount part.

Figure 7 is a back perspective view of the second form of the nasal cannula of **Figure 4**, showing a removable breathable pad on the inner side of the face mount part that abuts the patient's face.

Figure 8 is a perspective view of a third form of the nasal cannula assembly of the present invention, particularly showing a gases flow manifold part that allows for the attachment of removable prongs.

Figure 9 is a perspective view of the third form of the nasal cannula assembly of the present invention, showing a strap and breathable pad fittable to the manifold part of **Figure 8**.

Figure 10 is a perspective view of a first form of removable prongs capable of being attached to the manifold part of **Figure 8**.

Figure 11 is a perspective view of a second form of removable prongs capable of being attached to the manifold part of **Figure 8**.

Figure 12 is a perspective view of a patient wearing the nasal cannula assembly of **Figure 4**, showing the use of a neck tie to take some weight of the tubing and a head strap assisting in the maintaining of the assembly to the patient's face.

Figure 13 is a front view of a patient wearing a nasal cannula assembly present invention where the assembly is held to the patient's face with the assistance of ear loops.

Figure 14 is a side view of the patient and nasal cannula assembly of **Figure 13**.

Figure 15 is a perspective view of a tracheostomy fitting.

Figure 16 is a front view of a patient with a tracheostomy and fitting attached to a breathing supply where a neck tie or lanyard is used to support the conduit supplying gases to the patient.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0016] Whether used in a hospital environment or in a home environment, the nasal cannula assembly of the present invention will generally have associated three main pieces of apparatus. Firstly an active humidifier that controls the temperature of a heater plate heating a body of water to achieve a desired temperature and humidity of the gases being humidified. Secondly a transport conduit from the humidifier to the patient is also required, which is preferably heated to reduce condensation, or "rain out". Thirdly a nasal cannula designed to fit into the nasal cavity of a patient or user and deliver humidified, pressurized gases.

[0017] Referring to **Figure 1** a humidifying circuit as might be used with the nasal cannula of the present invention is shown. A patient 1 is receiving humidified and pressurized gases through a nasal cannula 20 connected to a humidified gases transportation pathway or inspiratory conduit 3 that in turn is connected to a humid-

ifier 8 (including humidification chamber 5) that is supplied with gases from a blower 15 or other appropriate gases supply means. The inspiratory conduit 3 is connected to the outlet 4 of a humidification chamber 5 which contains a volume of water 6. Humidification chamber 5 is preferably formed from a plastics material and may have a highly heat conductive base (for example an aluminium base) which is in direct contact with a heater plate 7 of humidifier 8. The humidifier 8 is provided with control means or electronic controller 9 which may comprise a microprocessor based controller executing computer software commands stored in associated memory. Gases flowing through the inspiratory conduit 3 are passed to the patient by way of the nasal cannula 20.

[0018] Controller 9 receives input from sources such as user input means or dial 10 through which a user of the device may, for example, set a predetermined required value (preset value) of humidity or temperature of the gases supplied to patient 1. In response to the user set humidity or temperature value input via dial 10 and other possible inputs such as internal sensors that sense gases flow or temperature, or by parameters calculated in the controller, controller 9 determines when (or to what level) to energise heater plate 7 to heat the water 6 within humidification chamber 5. As the volume of water 6 within humidification chamber 5 is heated, water vapour begins to fill the volume of the chamber above the water's surface and is passed out of the humidification chamber 5 outlet 4 with the flow of gases (for example air) provided from a gases supply means or blower 15 which enters the chamber through inlet 16. It should be noted that it is possible to obtain the relationship between the humidity of the gases in humidification chamber 5 and the temperature of the heater plate 7. Accordingly, it is possible to utilise the heater plate temperature in an algorithm or a look-up table to determine the humidity of the gases.

[0019] The blower 15 may be provided with a variable speed pump or fan 2 which draws air or other gases through the blower inlet 17. The speed of variable speed pump or fan 2 may be controlled by a further control means or electronic controller 18 (or alternatively the function of this controller 18 could be carried out by the other controller 9) in response to inputs from controller 9 and a user set predetermined required value (preset value) of pressure or fan speed via dial 19.

[0020] A heating element 11 may be provided within the conduit or tubing 3 to help prevent condensation of the humidified gases within the conduit. Such condensation is due to the temperature of the walls of the conduit being close to the ambient temperature, (being the temperature of the surrounding atmosphere) which is usually lower than the temperature of the humidified gases within the conduit. The heater element is effectively replaces the energy lost from the gases through conduction and convection during transit through the conduit. Thus the conduit heater element ensures the

gases delivered are at an optimal temperature and humidity.

Side Entry Nasal Cannula

[0021] The nasal cannula assembly of the present invention provides a patient with a patient interface suitable for the delivery of high airflow, high humidity gas flow to the patient's nasal cavity. A particular aspect of the nasal cannula of the present invention is the suitability for long term therapy where the patient, for example, a patient suffering from Chronic Obstructive Pulmonary Disease (COPD), will wear the cannula for several hours per day over weeks, months and in some cases years. Therefore, for patient's to accept use of nasal cannula under these circumstances the cannula need to be unobtrusive, comfortable to wear, noise free, suitable for wearing while sleeping, easy to clean and have prongs that can generate Positive End Expiry Pressure (PEEP). The cannula of the present invention may also be used for other therapies such as for Continuous Positive Airway Pressure (CPAP) therapy and the like.

[0022] A first form of the nasal cannula assembly of the present invention is shown in Figures 2 and 3. This nasal cannula, generally indicated as 20, comprises a face mount part 21 including a pair of tubular nasal prongs 22, 23 integrally molded with or removably attached to the face mount part 21, and a gases flow manifold part 24 that is integrally molded with or attached to tubing 3, such as that described above.

[0023] The face mount part 21 and prongs 22, 23 are preferably moulded from silicone or other flexible material as is known in the art of cannula construction. The gases flow manifold part 24 is preferably made from a hard plastics material, although it may be manufactured in other suitable materials.

[0024] The face mount part 21 is preferably integrally molded with the prongs 22, 23 and is shaped to generally follow the contours of a patient's face around the upper lip area. The inner side (not shown) of the face mount part 21 may be provided with a breathable pad, to be described below. The outer side 25 of the face mount part 21 has moulded in it an elongated oval recess 26 and two oval recesses 27, 28 that extend through the face mount part 21 and each meet the tubular passageway's formed within each of the tubular prongs 22, 23.

[0025] The gases flow manifold part 24 is generally tubular in shape having a substantially circular inlet (not shown) on one side that curves around to an elongated oval outlet 29. The circular inlet receives the end of the conduit or tubing 3, so that gases are supplied to the gases flow manifold part 24 and are able to flow through the inlet and out the outlet 29. The tubing 3 is preferably permanently fixed to the manifold part 24, but may be releasably attachable.

[0026] The outlet 29, being elongated and oval in shape, fits into the elongated recess 26 in a friction or

snap fit engagement with the manifold 21, such that a substantial force is required to remove the manifold part 24 from the elongated recess 26. Further, as the face mount part 21 is flexible and the manifold part 24 made from a harder plastics material it is possible for the manifold part outlet 29 to be easily pushed or forced into the elongated recess 26. When the manifold part 24 is engaged with the face mount part 21 and in use, gases flow from the tubing 3, through the gases flow manifold part 24 out its outlet 29, into each of the oval recesses 27, 28, into each of the prongs 22, 23 and into the patient's nares.

[0027] The face mount part elongate recess 26 and manifold part outlet 29 are symmetrical in shape and configuration and therefore the manifold part 24 is capable of being switched or flipped such that the tubing 3 extends from either the left or right side of the patient's nares. This means that the nasal cannula assembly 20 and associated tubing 3 are relatively unobtrusive as the cannula 20 only requires a single horizontal side entry, not two entries as that of the prior art.

[0028] The nasal cannula assembly of the present invention is more comfortable to wear as it sits under the septum of the nose and supports the two nasal prongs. As the prongs are made in one moulding of a soft material such as silicone the prongs are easy to insert in the patient's nares and comfortable to the patient.

[0029] For a nasal cannula assembly to be suitable for wearing during sleep each night the cannula must be noise free. Many prior art cannulas are prone to whistling. With a range of airflows generally being between 0 to 40 litres per minute, although airflows of 60 litres per minute are envisaged for the present nasal cannula, and with the air or gases being supplied to a single horizontal entry point it has proved difficult to prevent whistling. For this reason the face mount part 21 is contoured such that the pressure distribution within the face mount part 21 forces even airflows up each nasal prong.

[0030] As the nasal cannula assembly of the present invention is likely to be used while a patient is sleeping, the cannula must be easily tailored for the patients sleeping arrangement. The cannula of the present invention supplies high flow humidified gases to the patient from either the left side or the right side of the cannula thus allowing the minimum length connection circuit to the bedside unit supplying the humidified gas. As the nasal cannula assembly of the present invention allows for the horizontal entry of gases from either side the patient can configure the unit as left or right entry for their particular sleeping arrangement. It is envisaged that the tubing 3 is approximately two meters in length to allow for added flexibility of the cannula.

[0031] Reference is now made to Figures 4 to 7 that show a second form of the nasal cannula assembly of the present invention. In this form the nasal cannula assembly 30 is of a substantially similar form to the first form described above in relation to Figures 2 and 3, and has a face mount part 32, a pair of nasal prongs 33, 34,

gases flow manifold part 35 and tubing 3. The face mount part 32 and pair of nasal prongs 33, 34 are preferably integrally molded as one piece from a soft plastics material such as silicone, although in other forms the face mount part and prongs may be separate, but capable of attachment together for use.

[0032] The nasal prongs 33, 34 are tubular in shape and may be consistent in diameter but may be shaped to fit the contours of the human nares.

[0033] A strap or strap attachment means 31 may be integrally formed or attached to the face mount part 32 in order to enable the nasal cannula assembly 30 to be held in place about a patient's face.

[0034] The face mount part 32 has an open tubular recess 38 extending below the nasal prongs 33, 34 that is capable of receiving a gases flow manifold part 35 that is attached to or integrally formed with tubing 3. The tubular passageways within the nasal prongs 33, 34 extend through the face mount part and into the recess 38. The gases flow manifold part 35 is blocked at one end 39 but attached to the tubing at the other end and has an elongate opening 37 that acts as an exit for gases received from the tubing 3. Due to the flexible nature of the material the face mount part 32 is made from, and as the gases flow manifold part 35 is made from a hard plastics material, the gases flow manifold part 35 can be pushed through the tubular recess 38 in the face mount part 32 and the elongate opening 37 in the gases flow manifold part 35 meets with the tubular passageways of the prongs 33, 34. Therefore, in use, gases flowing through the tubing and into the gases flow manifold part 35 exit through the opening 37 and into the tubular passageways in the prongs 33, 34, then into the patient's nares.

[0035] In order to assist with maintaining the gases flow manifold part 35 within the manifold recess 38 the manifold part 35 is provided with an inner recessed portion 60 and contoured lip areas 58, 59. When engaged with the face mount part 32 the tubular body forming the recess 38 sits within the inner recessed portion 60 and the edges of the tubular body about the lips 58, 59 formed on the manifold part 35.

Breathable Pad

[0036] A breathable pad may be supplied with any of the nasal cannula assemblies described above. In particular, such a pad 36 is shown in Figure 7 in the second form of the nasal cannula assembly as described above. It must be appreciated that a pad of this type may be provided with any of the other two forms as herein described.

[0037] The pad is preferably attached to the inside surface of the face mount part 32 that connects with the upper lip of the patient wearing the cannula. The pad 36, which is preferably made from an absorbent cloth, reduces the incidence of heat and moisture on the patient's upper lip, where the face mount part 32 sits

against their face.

[0038] The pad 36 is preferably attached to the face mount part 32 by adhesive, for example, the pad could be supplied with a sticky backing that adheres to the face mount part, so that the pad can be easily removed from the face mount part and replaced as necessary.

[0039] The pad reduces the effects of heat against the patient's skin and improves hygiene, as any contaminants or cultures that may grow close to the patient's skin, in the warm environment can be removed on removal and replacement of the pad.

Three Part Nasal Cannula

[0040] Referring now to Figures 8 to 11, a third form of the nasal cannula assembly of the present invention is shown where the nasal cannula assembly comprises three parts.

[0041] Firstly, a gases flow manifold part 40 is shown in Figure 8 which is designed for either left or right hand orientation and provides a symmetrical flow to a pair of nasal cannula assembly prongs 41, 42 (see Figures 10 or 11).

[0042] Next, a pair of soft nasal prongs 41 or 42 are provided that are capable of being attached to the top of the gases flow manifold part 40 allowing for a large range of different shaped and spaced prongs to be available to the patient. Two such configurations of prongs 41, 42 are shown in Figures 10 and 11. The prongs 41 of Figure 10 are narrow elongate tubular members 43, 44 of a substantially constant diameter that are fittable into a patient's nares. The prongs are integrally molded with a body 45 that is fittable with the gases flow manifold part 40 (see Figure 8) by appropriate means, for example, friction or snap fit. The prongs 42 of Figure 11 are tapered tubular members 46, 47 moulded to a body 48. Again, this body 48 is capable of being fitted (friction, snap or other) to the gases flow manifold part of Figure 8. These prongs are preferably made from a soft plastics material such as silicon, although other suitable materials may be used.

[0043] With the prongs being removable they are easily cleaned and could also be disinfected for second or subsequent use.

[0044] The third part to the third form of the nasal cannula assembly shown in Figures 8 to 11 is the face mount part 49 of Figure 9. The face mount part 49 comprises a head strap 53 attached to a pad 50, that may be a moulded or shaped substantially rigid pad, for example, made from a plastics material such as polypropylene. The pad 36 may include a breathable cloth pad on its surface that abuts a patient's face, similar to that pad 36 described in relation to Figure 7, or the head straps 53 may extend to sit behind the pad. The head strap 53 is preferably made from a flexible material, such as neoprene.

[0045] The plastic pad 50 is shown in Figure 9 and has a plurality of apertures 61 formed into to allow for

heat and moisture to dissipate from the patient's facial surface. The pad 50 has fastening means 51, 52 for holding the gases flow manifold part 49 in the correct position on the upper lip of the patient. The fastening means may be clips 51, 52 that are fittable into complementary recesses 54, 55, 56, 57 provided in or on the manifold part 40 (see Figure 8), but other appropriate fastening means may be provided with the cannula. An example of other fastening means is a loop that is integrally moulded as part of the prongs which wraps around the face mount part and latches over a protrusion on the manifold part thus encapsulating the face mount part and holding the assembly together stably and securely. Another example of a fastening means is a plastic Velcro™ type attachment where one side would attach to one side of the manifold part 40 and the other side to the plastic pad 50. For the fastening means shown in Figures 8 and 9 at least one recess must be provided on either side of the manifold 40. In the preferred form of the nasal cannula assembly two recesses 54, 55 are provided on one side of the manifold 40 and two other recesses 56, 57 on the other side of the manifold 40.

[0046] The attachment between the face mount part 49 and the manifold part 40 allows for either left or right hand orientation of the manifold part and associated tubing.

[0047] It is envisaged the cannula of the present invention will be reusable for several wearings on a single patient and as such the nasal cannula assembly must be hygienic. It is envisaged that all the embodiments of the nasal cannula assembly of the present invention as herein described can be disassembled so that the cannula is easier to clean. The prongs and integrally attached parts are capable of being stored in a sterile solution until reused, much like false teeth are currently stored while not in use.

[0048] With a single flow entry cannula there will be less condensate due to the reduction in surface area for heat loss and thus the cannula of the present invention reduces the effects of condensation building in the tubing and cannula.

[0049] The detachable nasal cannula assembly described in relation to Figures 8 to 11 allows a patient on long-term therapy to order their particular prong size but maintain a common tubing connection system right to the point of connection into the manifold under the nose.

[0050] In other forms of the nasal cannula assembly of the present invention the assembly may only be provided with one nasal prong fittable into only one of the patient's nares. The purpose of such an assembly with one prong is to allow for consecutive use of a nasogastric tube. Nasogastric tubes are generally inserted in one of a patient's nares and extend down into their stomach. For example, it may be necessary or ideal for a patient to be fed by way of a nasogastric tube and to also receive heated humidified gases. The nasal cannula assembly of the present invention having only one prong would allow this.

Flexible Extension Dry Tube

[0051] Often an unheated flexible section of tubing is placed proximal to the patient to reduce torsion or pulling on the patient interface and reduce possible heat problems or over heating close to the patient. In order to reduce condensate forming in the unheated tubing, tubing can be provided that has vapour transmission properties. Referring now to Figure 12 the nasal cannula of the present invention (in particular, that of the second form described herein) may be provided with a short piece of breathable tubing 62 between the nasal cannula 30 and heated tubing 3. The tubing 62 is preferably made from a material that allows for transmission of water, such as a hydrophilic material, for example SYMPATEX™.

[0052] Test results show the performance of a 420mm length of breathable tube, operating with air input at an absolute humidity of 42.2 mg/L, an airflow of 10 litres per minute, in a room with ambient air at 22 degrees C and 50% RH, only lowered the air temperature to 37 and the absolute humidity to 41.15 mg/L at the exit of the dry tube. In comparison a 420mm length of non-breathable but insulated polyethylene tube under exactly the same conditions also output air at 41.15 mg/L. In the breathable tube there was significantly less condensate measured, therefore, some of the humidity that would otherwise be lost as condensate on the wall is being transmitted through the breathable wall.

[0053] The result of providing the short section of breathable tubing 62 is that a majority of humidity in the gases is transported to the patient, and there is an insignificant and immeasurable loss of humidity through the breathable wall of the short tube 62, while condensate is reduced. The design of the high airflow high humidity system has been optimized to deliver a breathable gas treatment to patients at temperatures approximating body temperature and fully saturated with water vapour for long treatment periods. The use of an unheated breathable conduit proximal to the patient to provide a connection that is highly flexible and avoids condensation by breathing would be expected to lower the humidity of the gas treatment thereby decreasing the efficacy of the treatment. These results are surprising and are counterintuitive and go some way to explaining why the use of a breathable tube as a short section of tubing before the patient has been overlooked. This short tube 62 is envisaged to be used with any tube delivering heated and humidified gases to a patient.

Neck Tie

[0054] A neck tie or lanyard may be provided with the nasal cannula assembly of the present invention. Figure 12 shows such a tie 63. The tie 63 is preferably connected to the tubing 3 or connection 67 between the tubing 3 and breathable tube 62. A toggle 64 is preferably provided with the neck tie 63 in order to adjust the neck tie's length. The neck tie has the purpose of taking some of

the weight of the tubing 3 and prevents the weight of the tubing 3 pulling on the nasal cannula assembly 30. This helps to prevent the prongs interfering with the very sensitive lining of the nasal passages. The loose fitting neck tie also provides a convenient way of connecting the tubing 3 to the patient outside the blankets. This allows the patient to turn in the bed and avoids the tubing 3 overheating if placed under the blankets.

[0055] The tie or lanyard described may be used with any breathing apparatus that supplies gases to a patient; for example it may be used with a nasal or face mask or with a tracheostomy fitting or connector. When the tie or lanyard is used with such apparatus it takes the weight of the conduit(s) or tubing supplying gases to the mask, connector or cannulae and helps reduce the pull on the mask, connector or cannulae.

[0056] Figures 15 5 and 16 show a tracheostomy fitting or connector that may utilise a neck tie or lanyard of the present invention. The tracheostomy connector 69 attaches to a tracheostomy mount 72 that extends into a tracheostomy tube (not shown) through hole in a patient's 68 neck and into their airway passages. The connector 69 provides a direct coupling of a tracheostomy tube to the breathing supply of gases received through a conduit 71. Preferably the conduit 71 is constructed in a breathable material, similar to that described above, but may be a heated tube.

[0057] The connector 69 has the conduit 71 attached directly to it and also includes an expiratory port 70 to allow for expiration of gases. On inspiration no gases flow occurs out the port 70 due to the flow of gases to the connector 69 being greater than a patient's peak inspiratory flow. Therefore, there is also no or very little entraining of gases from the ambient air.

[0058] Excess weight on the tracheostomy tube may cause excess movement of the tube, with the risk of complications such as displacement or recannulation of the tracheostomy, the formation of granulation tissue or more seriously, stomal erosion. To obviate or reduce these problems a tie or lanyard 73 can be connected to the conduit 71 or additional connector 74. (that may for example connector the conduit 71 to an additional conduit 75 that supplies gases). The tie or lanyard 73 transfers the weight of the conduits 71, 75 and connector 74 from the tracheostomy tube or mount 72 and distributes it onto the neck of the patient leaving a minimal load directly on the tracheostomy tube or mount 72. Preferably the tie or lanyard 73 is adjustable so that the tie or lanyard length can be altered to suit a patient's requirements.

Ear Loops

[0059] Orientation of a nasal cannula is an essential requirement to patient comfort. If the nasal cannula is not held firmly in position, it can skew, placing unwanted load on the inside surfaces of the patient's nares. However, to overcome this head gear is often provided with

nasal cannula, although, if the head gear is not tight the nasal cannula can still move. This type of tight tension can then compromise patient comfort with pressure on the head and face, while forcing the cannula further up the patient's nose. Ideally nasal cannula should attach to the patient's face in a rigid manner, yet with low loading on the head and face.

[0060] Referring to Figures 13 and 14 nasal cannula attachment means may be provided to hold the nasal cannula assembly 30 to the patient's face. The attachment means are preferably ear loops 65, 66 that are connected to the straps 31 of the face mount part 32 of the nasal cannula assembly 30.

[0061] The loops 65, 66 extend from the face mount part 32 around the patient's ears, and provide rigid anchoring when an inelastic material is used. The loops 65, 66 are preferably made from a thin, round cord with the ends captured in plastic, and are preferably adjustable. The plastic ends of the loops 65, 66 are inserted into purpose made cavities in the straps 31, enabling adjustment of length for a comfortable, yet firm fit.

[0062] In use, to fit the nasal cannula assembly, a first loop (for example, loop 65) is placed over one ear, the nasal cannula assembly positioned on the patient's face and in their nose, then the other ear is passed through the second loop (for example, loop 66), so both loops sit snugly behind the ears. This method of fitting the nasal cannula avoids the initial discomfort of gases being blown into the patient's eyes when the cannula assembly is pulled down the face for fitting with other headgear. Fastening the nasal cannula in this method provides an attachment means that is horizontally secure with minimum tension applied to the ear connection loops. The ear loops have the added advantage for a patient lying on their back that there are no straps behind the back of the head that are moved by head movement on the pillow.

[0063] The features disclosed in the foregoing description, in the claims and/or in the accompanying drawings may, both separately and in any combination thereof, be material for realising the invention in diverse forms thereof.

Claims

1. A nasal cannula assembly adapted to deliver gases to a patient (1) by way of a gases transport means (3) comprising:

a face mount part (21), including at least one nasal prong (22, 23) capable of being fitted into at least one of said patient's nares,
a removable gases flow manifold part (24) in use in fluid communication with said face mount part (21), said manifold part (24) having a single horizontal side gases entry, in use, in fluid communication with said transport means (3).

2. A nasal cannula assembly according to claim 1 wherein said gases flow manifold part (24) is capable of being fitted with said face mount part (21) in two configurations, a first configuration where said transport means (3) extends to the left of said nasal cannula assembly and a second configuration where said transport means (3) extends to the right of said nasal cannula assembly.
3. A nasal cannula assembly according to claim 1 or 2 wherein said gases flow manifold part (24) terminates at an open recess (29) that in use is aligned with a complementary recess (26) in said face mount part (21) thereby providing gases flow to said at least one nasal prong (22, 23) and said at least one of said patient's nares.
4. A nasal cannula assembly according to any one of claims 1 to 3 wherein said face mount part (21) and said at least one nasal prong (22, 23) are integrally moulded from a soft plastics material.
5. A nasal cannula assembly according to any one of claims 1 to 3 wherein said at least one prong (22, 23) is detachable from said face mount part (21) to allow different sized prongs to be placed on said face mount part (21) to suit different sized patients.
6. A nasal cannula assembly according to any one of claims 1 to 4 wherein said nasal cannula assembly includes a breathable pad (36) attached to the inner side of said face mount part (21), such that in use said pad (36) abuts said patient's face in the upper lip region.
7. A nasal cannula assembly according to claim 6 wherein said pad (36) is removable from said face mount part (21).
8. A nasal cannula assembly according to any one of claims 1 to 8 wherein said nasal cannula assembly includes two nasal prongs (22, 23).
9. A nasal cannula assembly according to any one of claims 1 to 8 wherein said nasal cannula assembly is attached to said gases transport means (3) by way of a breathable tube (62).
10. A nasal cannula assembly according to claim 9 wherein said breathable tube (62) is a short section of tubing constructed of a breathable or hydrophilic material.
11. A nasal cannula assembly according to any one of claims 1 to 10 wherein said nasal cannula assembly is attached to said patient (1) with attachment means (65, 66) that loop about said patients' ears.
12. A nasal cannula assembly according to any one of claims 1 to 11 wherein said gases flow manifold part (24) is made from a hard plastics material.
13. A breathing assistance apparatus comprising:
 - a pressurised source of gases (15),
 - humidification means (5) adapted to, in use, be in fluid communication with said source of gases and adapted to in use humidify said gases,
 - humidified gases transport means (3) adapted to, in use, be in fluid communication with said humidification means (5) and adapted to in use convey said humidified gases,
 - heating means (11) disposed within said transport means (3) and adapted to in use heat said gases as they pass through said transport means (3), and
 - nasal cannula (20), adapted to deliver said humidified gases to said patient (1), said nasal cannula (20) comprising a face mount part (21), including at least one nasal prong (22, 23) capable of being fitted into at least one of said patient's nares, a removable gases flow manifold part (24) in use in fluid communication with said face mount part (21), said manifold part (24) having a single horizontal side gases entry, in use, in fluid communication with said transport means (3).
14. A breathing assistance apparatus according to claim 13 wherein said heating means (11) comprises a heater wire (11) disposed within, throughout or around said transport means (3).
15. A breathing assistance apparatus according to any one of claims 13 or 14 including a means for supporting the weight of said heated transport means including a loose fitting adjustable tie (63) locatable about said patient's neck.
16. A breathing assistance apparatus according to claim 13 to 15 wherein said gases flow manifold part (24) is capable of being fitted with said face mount part (21) in two configurations, a first configuration where said transport means (3) extends to the left of said nasal cannula assembly (20) and a second configuration where said transport means (3) extends to the right of said nasal cannula assembly (20).
17. A breathing assistance apparatus according to any one of claims 13 to 16 wherein said face mount part (21) and said at least one nasal prong (22, 23) are integrally moulded from a soft plastics material.
18. A breathing assistance apparatus according to any one of claims 13 to 16 wherein said at least one

prong (22, 23) is detachable from said face mount part (21) to allow different sized prongs to be placed on said face mount part (21) to suit different sized patients.

19. A breathing assistance apparatus according to any one of claims 13 to 18 wherein said nasal cannula assembly (20) includes a breathable pad (36) attached to the inner side of said face mount part (21) such that in use said pad (36) abuts said patient's face in the upper lip region. 10
20. A breathing assistance apparatus according to any one of claims 13 to 19 wherein said nasal cannula assembly (20) is attached to said gases transport means (3) by way of a breathable tube (62). 15
21. A breathing assistance apparatus according to claim 20 wherein said breathable tube (62) is a short section of tubing constructed of a breathable or hydrophilic material. 20
22. A breathing assistance apparatus according to any one of claims 13 to 21 wherein said nasal cannula assembly (20) is attached to said patient (1) with attachment means (65, 66) that loop about said patients' ears. 25
23. A breathing assistance apparatus according to any one of claims 13 to 22 wherein said gases flow manifold part (24) is made from a hard plastics material. 30
24. A conduit support apparatus for a breathing assistance apparatus to supply gases to a patient (68) by way of at least one conduit (71, 75) comprising: 35
 - a tie or lanyard (73) capable of being placed about said patient's neck, said tie or lanyard (73) being connected to said at least one conduit (71, 75) such that said tie or lanyard (73) supports the weight of said at least one conduit (71, 75). 40
25. A conduit support apparatus according to claim 24 wherein said breathing assistance apparatus is one of a mask, a nasal cannula assembly (20) or a tracheostomy connector (69). 45
26. A conduit support apparatus according to claim 24 wherein said breathing assistance apparatus comprises a nasal cannula assembly (20) adapted to deliver gases to a patient comprising: 50
 - a face mount part (21), including at least one nasal prong (22, 23) capable of being fitted into at least one of said patient's nares, 55
 - a removable gases flow manifold part (24) in use in fluid communication with said face mount

part (21), said manifold part (24) having a single horizontal side gases entry, in use, in fluid communication with said at least one conduit (71, 75).

27. A conduit support apparatus according to claim 24 wherein said at least one conduit (71, 75) is at least partially a heated breathing tube (3). 5




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8

FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12






FIGURE 14

FIGURE 13



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.